

# BZ Series

Horizontal Laminar Airflow Workstation



ACCU-CHART®



Accurate Medicine Through Barcodes

# The BZ Series of Horizontal Laminar Flow Hoods


are designed for the handling of materials in a sterile working environment. The work area is continuously bathed with positive pressure ISO 5/Class 100 horizontal laminar flow air that has passed through a High Efficiency Particulate Air (HEPA) filter. This filter removes organisms and particulates 0.3 micron in size with an efficiency of 99.99%. The laminar airflow principle consists of moving individual streams of unidirectional, ultra-clean air along parallel lines with minimal turbulence. The HEPA filter is positioned in the rear of the work area and is protected by a removable, perforated aluminum diffuser.



# Compliant

## Stainless Steel Construction, Ergonomic Design

The BZ Laminar Flow Cabinet is constructed of quality all-welded stainless steel with a pharmaceutical grade finish. The fluorescent light housing is externally mounted to provide optimum lighting into the work area. The acrylic top and side panels allow for additional ambient light and visibility into the work area. Our SpillGuard feature is utilized in the sides and back of the full-width work area. The CurveFlex™ forearm support feature provides operator comfort.





External Fluorescent Lighting

I.V. Bar with Hooks

Stainless Steel Framed Acrylic Panels for Maximum Visibility

Spillguard to Protect HEPA Filter

Cleanroom-Compliant Prefilter increases the life of the front loading HEPA Filter while reducing particulates inside the cleanroom

# Standard Features

## Overall Dimensions:

BZ-3SSRX: 37" wide x 34" deep x 49½" high

BZ-4SSRX: 49" wide x 34" deep x 49½" high

BZ-6SSRX: 73" wide x 34" deep x 49½" high

BZ-8SSRX: 97" wide x 34" deep x 49½" high

## Work Area Dimensions:

BZ-3SSRX: 34" wide x 22" deep x 34" high

BZ-4SSRX: 46" wide x 22" deep x 34" high

BZ-6SSRX: 70" wide x 22" deep x 34" high

BZ-8SSRX: 94" wide x 22" deep x 34" high

**Electrical:** 115V / 60 Hz (220V / 50-60 Hz also available)

Conforms to ANSI/UL STD 61010-1 Certified to CAN/CSA C22.2





Bin Cart for Storage Under Workdeck  
30" W x 26.5" D x 29" H (Includes 12 Bins)

Duplex Outlet  
in Work Area



Stopcock for  
Air, Gas or Vacuum

Programmable Electrical  
Stand Height Adjustment



Stainless Steel  
Side Panels

# Accessories & Options




Stainless Steel Stand  
30" or 36" High



Drawers Under  
Workdeck can be  
Mounted on Right,  
Left or Both Sides



Sealed Data  
Port Passage



**Accu-Chart®**

1305 Remington Rd. Suite I Schaumburg, IL 60173  
Ph: 847-252-7183 847-252-7300 Fax: 630-307-5982  
[www.accuchart.com](http://www.accuchart.com)